


PTFE GLASSCLOTH

PTFE GLASSCLOTH RGA106-2 is a Premium Grade PTFE-coated fabric with a high performance, silicone pressure-sensitive adhesive on one side. It has an exceptionally smooth surface to give superior release properties in the most demanding areas.

PTFE GLASSCLOTH RGA106 -2 is used extensively in the packaging industry for heat sealing and wrapping applications, for tool and mould release linings and as a cover on welding platens and drying rollers.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
Base Thickness:	mm	0.150	FTMS 191A-5030
Adhesive Thickness:	mm	0.045	FTMS 191A-5030
Base PTFE-fabric weight:	g/m ²	315	FTMS 191A-5041
180° Peel Adhesion:	N/cm	6.3	ASTM D3330-83
Tensile Strength:	N/cm	310 x 300	FTMS 191A-5102
Adhesive Type:	-	Silicone	-
Temperature Resistance:	°C	-73 to +260	-
Standard Width:	mm	1000	-

TECHPLAS UK



RGA106-2

Techplas UK Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes,
Cheshire, WA8 0RZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:
carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.