


PTFE GLASSCLOTH

PTFE GLASSCLOTH RGP010 AS is a premium grade PTFE-coated woven glass fabric with anti-static properties. It provides excellent release (“non-stick”) properties and wear characteristics over wide temperature ranges where static dissipative properties are required.

PTFE GLASSCLOTH RGP010 AS is typically used as a fuse pressing belting material where anti-static performance is required, and also a release sheet for use in the production of wood and composite panels.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
Weight:	g/m ²	500	FTMS 191A-5041
Thickness:	mm	0.235	FTMS 191A-5030
Tensile Strength:	N/cm	540 x 500	FTMS 191A-5102
Trap Tear Strength:	N	54 x 55	FTMS 191A-5136
Surface Resistivity:	Ω/ Square	<1 x 10 ⁶	ASTM D257-78
PTFE Content:	%	60	-
Temperature Resistance:	°C	-150 to +260	-
Standard Widths:	mm	1525, 2000, 2600	-



RGP010 AS

Techplas UK Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes,
Cheshire, WA8 0RZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:

carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.

TECHPLAS UK