


PTFE GLASSCLOTH

PTFE GLASSCLOTH RGP205 AS is an anti-static PTFE-coated fibreglass fabric. It possesses excellent release properties and chemical resistant properties.

PTFE GLASSCLOTH RGP205 AS is typically used as a release liner in the packaging and plastics industries where static dissipation is required.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
Weight:	g/m ²	250	FTMS 191A-5041
Thickness:	mm	0.120	FTMS 191A-5030
Tensile Strength:	N/cm	300 x 280	FTMS 191A-5102
Trap Tear Strength:	N	20 x 18	FTMS 191A-5136
Surface Resistivity:	Ω/Square	<1 x 10 ⁶	ASTM D257-78
PTFE Content:	%	58	-
Temperature Resistance:	°C	-150 to +260	-
Standard Widths:	mm	1000; 1525	-

TECHPLAS UK



RGP205 AS

Techplas UK

Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane,
Widnes, Cheshire, WA8
ORZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

E-mail:

carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made