


PTFE POROUS GLASSCLOTH

PTFE POROUS GLASSCLOTH RGPOR910-1 is a light PTFE-coated fibreglass fabric which provides controlled porosity.

PTFE POROUS GLASSCLOTH RGPOR910-1 is typically used in applications such as composite moulding and curing applications.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
Weight:	g/m ²	240	FTMS 191A – 5041
Thickness:	mm	0.195	FTMS 191A – 5030
Tensile Strength:	N/cm	380 x 300	FTMS 191A – 5102
PTFE Content:	%	15	-
Temperature Resistance:	°C	-150 to +260	-
Standard Widths:	mm	1000, 1525	-

TECHPLAS UK



RGPOR910-1

Techplas UK Performance Plastics sales fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes, Cheshire, WA8 0RZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:

carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.